



Modified Ohio Hazardous Waste Facility Installation and Operation Permit

Division of Environmental Response and Revitalization

Permittee: Clean Harbors Recycling Services of Ohio, LLC U.S. EPA ID: OHD 980 587 364
Facility Name: Clean Harbors Recycling Services of Ohio, LLC
Mailing Address: 581 Milliken Drive SE
City: Hebron State: OH Zip: 43025-9657
Operator Name: Clean Harbors Recycling Services of Ohio, LLC
Mailing Address: 581 Milliken Drive SE
City: Hebron State: OH Zip: 43025-9657
Facility Street Address: 581 Milliken Drive SE
City: Hebron State: OH Zip: 43025-9657

Permit Modification

This Modified Ohio Hazardous Waste Facility Installation and Operation Permit is issued pursuant and subject to Section 3734.05(I) of the Ohio Revised Code and Rule 3745-50-51(D) of the Ohio Administrative Code.

The Ohio Hazardous Waste Facility Installation and Operation Permit for the facility with the above-referenced ID number as issued by the Ohio Environmental Protection Agency and journalized on November 18, 2015, and as subsequently modified by the Ohio Environmental Protection Agency, is hereby incorporated by reference in its entirety, except as it may be modified herein. This modification of the permit shall remain in effect until such time as the Ohio Hazardous Waste Facility Installation and Operation Permit is renewed, modified, withdrawn, suspended, or revoked.

The Permittee shall comply with all requirements of the modified permit application as amended or supplemented on April 17, 2020 and July 27, 2020. The information contained in the modified permit application is incorporated herein by reference. Specifically, all written statements regarding the specifications, locations, or capabilities of the processes, equipment, containment devices, safety devices or programs, or other matters made by the applicant in the permit modification application are hereby incorporated as express, binding terms and conditions of this modified permit.

The modified Terms and Conditions of this permit are attached hereto and are incorporated herein by reference. The modified Terms and Conditions supersede and replace the corresponding pages found in the November 18, 2015 renewal permit.

Permit Modification Approval

A handwritten signature in blue ink that reads "Laurie A. Stevenson".

Date: 8/25/2020

Laurie A. Stevenson, Director
Ohio Environmental Protection Agency

Rule 3745-55-47 and as specified by the wording requirements of OAC Rule 3745-55-51.

During the life of the permit the facility may change the mechanism used to demonstrate liability coverage as stated in OAC Rule 3745-55-47. The facility must submit the liability mechanism documentation to the director of Ohio EPA in accordance with the parameters set forth in OAC Rule 3745-55-47.

- (f) Requirements for new container storage area No. 2D and modified container storage area No. 2B.

No hazardous waste shall be stored at the newly permitted area No. 2D of the facility and no more than 6,150 gallons of hazardous waste shall be stored in permitted area No. 2B of the facility until Ohio EPA, in accordance with OAC Rule 3745-50-58(L), has inspected such portions of the facility and finds that they are in compliance with all applicable rules, the terms and conditions of this permit, and the approved permit application.

A.28 Information to be Maintained at the Facility
OAC Rule 3745-54-74

- (a) Unless otherwise specified by the hazardous waste rules, the Permittee must maintain at the facility, until closure is completed and certified by an independent, registered professional engineer, pursuant to OAC Rule 3745-55-15, and until the Director releases the Permittee from financial assurance requirements pursuant to OAC Rule 3745-55-43, the following documents (including amendments, revisions and modifications):
- (i) Waste analysis plan, developed and maintained in accordance with OAC Rule 3745-54-13 and the terms and conditions of this permit;
 - (ii) Contingency plan, developed and maintained in accordance with OAC Rule 3745-54-53 and the terms and conditions of this permit;
 - (iii) Closure plan, developed and maintained in accordance with OAC Rule 3745-55-12 and the terms and conditions of this permit;
 - (iv) Cost estimate for facility closure, developed and maintained in accordance with OAC Rule 3745-55-42 and the terms and conditions of this permit;
 - (v) Personnel training plan and the training records, developed and maintained in accordance with OAC Rule 3745-54-16 and the terms and conditions of this permit;
 - (vi) Operating record, required by OAC Rule 3745-54-73 and the terms and conditions of this permit; and
 - (vii) Inspection schedules, developed in accordance with OAC Rules 3745-54-15, 3745-55-74 and 3745-55-95 and the terms and conditions of this permit.
 - (viii) Post-closure plan, as required by OAC Rule 3745-55-18(A) and the terms and conditions of this permit.
 - (ix) Annually-adjusted cost estimate for facility closure and post-closure, as required by OAC Rules 3745-55-42 and 3745-55-44 and the terms and conditions of this permit.

- (x) All other documents required by Module A, Permit Condition A.12, and;
 - (xi) Ground water monitoring results and reports as required by OAC Rule 3745-54-74.
- (b) The Permittee must maintain copies of all inspection logs at the facility for a period not less than three (3) years from the date of inspection.

A.29 Waste Minimization Report
OAC Rules 3745-54-73 and 3745-54-75

- (a) The Permittee must submit a Waste Minimization Report describing the waste minimization program required by OAC Rules 3745-54-75(H), (I), and (J); 3745-54-73(B)(9); and 3745-52-20(A) at least once every five years. The provisions of OAC Rules 3745-54-75(H), (I) and (J); and 3745-54-73(B)(9) must be satisfied annually.
- (b) The Permittee must submit the Waste Minimization Report to Ohio EPA's Office of Compliance Assistance and Pollution Prevention within one hundred eighty (180) days of the effective date of this permit, and must submit updates to this report once every five years thereafter.

MODULE C - CONTAINERS STORAGE & TREATMENT

C. CONTAINER STORAGE AND MANAGEMENT

The Permittee operates six (6) storage areas for the storage of hazardous waste in containers (S01). The maximum amount of container storage allowed in Container Storage Area No. 1 is 158,400 gallons. The maximum amount of container storage allowed in Container Storage Area No. 2B is 13,200 gallons. The maximum amount of container storage allowed in Container Storage Area No. 2D is 19,360 gallons. The maximum amount of container storage allowed in Container Storage Area No. 2E is 8,070 gallons. The maximum amount of container storage allowed in Truck Station No. 1 is 13,200 gallons and the maximum amount of container storage allowed in Truck Station No. 2 is 13,200 gallons.

Container Storage Area No. 1 is constructed of a reinforced concrete pad with twelve inch high curbs at the east and west ends, and variable height curbs along the north and south ends (six inch minimum in the middle and increasing as the elevation of the pad decreases).

The secondary containment capacity of Container Storage Area No. 1 is 33,690 gallons. The pad is sloped with a one sixteenth-inch per foot slope to direct the flow of any leakage or spillage to sumps located at the east and west ends of the storage area. Each sump is twenty-four inches in diameter by two feet deep and has a capacity of 47 gallons. This storage area is covered by a roof to prevent precipitation from entering the storage area. Precipitation run-on is controlled by the dike surrounding the storage area.

Container Storage Area No. 2 is constructed of reinforced concrete and is divided into areas 2B, 2C, 2D and 2E. These areas are within an enclosed building, and there is a concrete berm to keep precipitation run-on away from the building. Area 2C is to be used for container staging only, and is not permitted for hazardous waste storage. Containers may be staged in area 2C for up to 24 hours before they must be moved to a permitted storage area. Area 2B has a secondary containment capacity of 1,426 gallons, Area 2D has a secondary containment capacity of 1,995 gallons, and Area 2E has a secondary containment capacity of 808 gallons.

Truck Station 1 and 2 are constructed of reinforced concrete with an average curb height of 4.5 inches. The floor slopes to a 43 cubic foot catch basin, and a 16 foot by 1-foot trench runs across each bay to the sump. The average depth of the trench is 4 inches. Truck Station No. 1 has a secondary containment capacity of 5,382 gallons and Truck Station No. 2 has a secondary containment capacity of 5,382 gallons. These areas are within an enclosed building, and the driveway into and out of the building slopes upward to keep precipitation run-on out of each area.

The waste codes listed in Permit Condition C.3(a) may be stored in containers. Ignitable waste is only permitted to be stored in Container Storage Areas No. 1, No. 2B, No. 2D, and No. 2E. The types and sizes of containers are described in Section 4 of the permit application.

C.1 Container Storage/ Quantity Limitation

- (a) The Permittee is authorized to store 225,430 gallons of hazardous waste at any given time in the Permitted Container Storage Areas No. 1, No. 2B, No. 2D, No. 2E, Truck Station No.1 and Truck Station No. 2.
- (b) For the purpose of compliance with the capacity limitation of this permit, each container will be considered to be storing an amount of hazardous waste equal to its capacity, regardless of the actual quantity stored in the container.

- (c) Permit Conditions C.1(a) and C.2 shall not apply to the Permittee's activities as a generator accumulating hazardous waste on-site in compliance with OAC Rule 3745-52-34 and 40 CFR Part 265, subparts AA, BB, and CC.

However, when accumulating waste within the permitted container storage area, in accordance with OAC Rule 3745-52-34 and 40 CFR Part 265, subparts AA, BB, and CC, the Permittee must not, for the total amount of hazardous waste stored and accumulated, exceed the maximum container storage inventory established under this permit condition.

C.2 Reserved

C.3 Waste Identification

The Permittee must store in containers only the hazardous waste codes specified below:

D001, D002, D004, D005, D006, D007, D008, D009, D010, D011, D018, D019, D021, D022, D023, D024, D025, D026, D027, D028, D029, D030, D032, D033, D034, D035, D036, D037, D038, D039, D040, D041, D042, D043, F001, F002, F003, F004, F005, F006, K006, K016, K022, K030, K048, K049, K050, K051, K052, K060, K085, K086, K087, K095, K096, K105, K141, K142, K143, K144, K145, K147, K148, U002, U003, U019, U031, U037, U044, U051, U052, U055, U056, U057, U068, U069, U070, U071, U072, U075, U077, U078, U079, U080, U083, U084, U108, U110, U113, U117, U118, U121, U124, U140, U154, U159, U161, U162, U165, U169, U171, U188, U191, U196, U210, U211, U213, U220, U226, U227, U228, and U239

C.4 Condition of Containers

OAC Rule 3745-55-71

If a container holding hazardous waste is not in good condition (e.g., severe rusting, apparent structural defects) or if it begins to leak, the Permittee must transfer the hazardous waste from such container to a container that is in good condition or otherwise manage the waste in compliance with the conditions of this permit and the hazardous waste facility chapters of the OAC.

C.5 Compatibility of Waste with Containers

OAC Rule 3745-55-72

The Permittee must use a container made of or lined with materials which will not react with, and are otherwise compatible with, the hazardous waste to be stored, so that the ability of the container to contain the waste is not impaired.

C.6 Management of Containers

OAC Rule 3745-55-73

- (a) The Permittee must keep all containers closed during storage, except when it is necessary to add or remove waste, and must not open, handle, or store containers in a manner which may rupture the container or cause it to leak.
- (b) In the event lab-pack wastes are generated they must be handled in compliance with applicable storage requirements.

- (c) In the event lab-pack wastes are generated they must be packaged in drums containing absorbent material that is compatible with the waste.

C.7 Containment Systems
OAC Rule 3745-55-75

- (a) The Permittee must maintain the containment system in accordance with the plans and specifications contained in Section 4 of the permit application.
- (b) The Permittee must maintain the containment system as described in the permit application, designed with sufficient capacity to contain ten percent of the total volume of the containers or the volume of the largest container, whichever is greater. The containment system must be free of cracks and gaps and sufficiently impervious to contain leaks and spills and accumulated precipitation until the collected material is detected and removed.
- (c) The base of the containment system must be sloped or the containment system must be otherwise designed and operated to drain and remove liquids resulting from leaks, spills, or precipitation, unless the containers are elevated or are otherwise protected from contact with accumulated liquids.
- (d) Run-on into the containment system must be prevented unless the collection system has sufficient excess capacity in addition to that required in Permit Condition C.7(b) above.
- (e) Spilled or leaked waste and accumulated precipitation must be removed from the sump or collection area in a timely manner. This time period is not to exceed twenty-four (24) hours from the time spilled and/or leaked waste is discovered to have reached the hazardous waste pad sumps.

C.8 Reserved

C.9 Inspection Schedules and Procedures
OAC Rules 3745-54-15 and 3745-54-73

The Permittee must inspect the container storage area in accordance with the inspection schedule contained in Section 6 of the permit application and in accordance with OAC Rule 3745-54-15. The inspection schedule must be designed to detect for leaking containers, deteriorating containers, and/or containment systems. The Permittee must note the results of these inspections in the inspection log along with any remedial action taken.

Areas subject to spills, such as loading or unloading areas, shall be inspected daily when in use pursuant to the inspection procedure described in Section 6 of the permit application. The Permittee must maintain these inspection results in the facility operating record.

C.10 Recordkeeping
OAC Rule 3745-54-73

The Permittee must comply with all recordkeeping requirements of OAC Rule 3745-54-73 as part of the facility operating record.

C.11 Special Container Provisions for Ignitable or Reactive Waste

OAC Rules 3745-54-17 and 3745-55-76

- (a) The Permittee must not store ignitable or reactive waste except in accordance with OAC Rules 3745-54-17 and 3745-55-76.
- (b) The Permittee must not locate containers holding ignitable or reactive waste within 15 meters (50 feet) of the facility's property line.
- (c) The Permittee must take precautions to prevent accidental ignition or reaction of ignitable or reactive waste and shall follow the storage procedures specified in Section 6.5 the permit application.

C.12 Special Container Provisions for Incompatible Waste

OAC Rules 3745-54-17(B) and 3745-55-77

- (a) The Permittee must not store incompatible waste except in accordance with OAC Rules 3745-54-17(B) and 3745-55-77.
- (b) The Permittee must not place hazardous waste in an unwashed container that previously held an incompatible waste or material.
- (c) The Permittee must separate or protect (by means of a dike, berm, wall, or other device) a storage container holding a hazardous waste that is incompatible with any waste or other materials stored nearby in other containers, piles, open tanks, or surface impoundments

C.13 Reserved

C.14 Closure and Post-Closure

OAC Rules 3745-55-10 through 3745-55-20, and 3745-55-78

At closure of the container area, the Permittee shall remove all hazardous waste and hazardous waste residues from the containment system, in accordance with the procedures in the closure plan set forth in Section 9 of the permit application.